

# OEG Hygienic storage tank 1,000 litres with 2 smooth-pipe heat exchangers



With this OEG hygienic storage tank, the highest demands on the hygiene of drinking water and energy efficiency are fulfilled. The structure of this tank is fundamentally different from usual, large-volume service water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water and - at the same time - serves as a powerful heat exchanger. Thus, the advantages of a buffer tank are combined with those of a hot water heater.

Only if needed, the drinking water flows through the corrugated stainless steel pipe in the water of the heated tank and the stratification of the heating water is not disturbed. This leads to a very low energy consumption and you can guarantee your customers legionella-free drinking water.

You do not need a legionella protection programme in the regulation. Consumers are provided with hygienically-clean, fresh water at their desired temperature at any time.

Due to the two additional smooth-pipe heat exchangers, two more heat generators can be integrated and their energy can be fed into the hygienic storage tank.

## General

OEG Nr.:	516005292
rated volume according to EN 12897:	1000
Colour:	silver
Insulation according to DIN 4102-1 Fire Protection Class B2:	removable A+ segment insulation
Weight [kg]:	355
Total height including insulation [mm]:	2310
Diameter without insulation [mm]:	790
Diameter with insulation [mm]:	1015
Tilt height [mm]:	2280

## Energy

Energy efficiency class according to EU regulation no. 812/2013:	A+
Heat loss according to EN 12897 [W]:	55
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	1,320
Output capacity (45°) [l]:	571
Performance indicator NL following DIN 4708:	6,40

## Tank

Real volume according to EN 12897 [l]:	985
$p_{\max}$ tank [bar]:	3
$t_{\max}$ tank [°C]:	95

## Domestic hot water heat exchanger

Domestic hot water heat exchanger area [m <sup>2</sup> ]:	8
Domestic hot water heat exchanger volume [l]:	34,20

# OEG Hygienic storage tank 1,000 litres with 2 smooth-pipe heat exchangers



---

$p_{\max}$ Domestic hot water heat exchanger [bar]:	6
$t_{\max}$ Domestic hot water heat exchanger [°C]:	95

---

## Smooth-pipe heat exchanger

---

Smooth-pipe heat exchanger [number]:	2
Smooth-pipe heat exchanger area bottom [m <sup>2</sup> ]:	3,30
Smooth-pipe heat exchanger area top [m <sup>2</sup> ]:	2,60
Smooth-pipe heat exchanger volume bottom:	21,30
Smooth-pipe heat exchanger volume top:	17
$p_{\max}$ Smooth-pipe heat exchanger [bar]:	10
$t_{\max}$ Smooth-pipe heat exchanger [°C]:	130

---

## Connections

---

Connection layout:	90°
Connection sensor [Ø mm / terminal]:	6mm
Connection cold / hot water:	Rp 1¼"
Connection heat generator [thread]:	Rp 1½"
Connection heat exchanger [thread]:	Rp 1"
Connection heating element [thread]:	Rp 1½"

---