


OEG Fresh-Water storage tank 800 l with 1 smooth-pipe heat exchanger



With this OEG hygienic storage tank, the highest demands on the hygiene of drinking water and energy efficiency are fulfilled. The structure of this tank is fundamentally different from usual, large-volume hot water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water and - at the same time - serves as a powerful heat exchanger. Thus, the advantages of a buffer tank are combined with those of a hot water heater.

Only if needed, the drinking water flows through the corrugated stainless steel pipe in the water of the heated tank and the stratification of the heating water is not disturbed. This leads to a very low energy consumption and you can guarantee your customers legionella-free drinking water.

You do not need a legionella protection programme in the regulation.

Consumers are provided with hygienically-clean, fresh water at their desired temperature at any time.

Due to the additional smooth-pipe heat exchanger, another heat generator can be integrated and its energy can be additionally fed into the hygienic storage tank.

Data pursuant to EU regulation 814/2013

Name of supplier's trade marks:	OEG GmbH
Model identification of the supplier:	516005470 - Fresh-Water storage tank 800 l with 1 smooth-pipe heat exchanger
Heat retaining losses in watts:	51
Storage tank volume in litres:	796

General

OEG Nr.:	516005470
Rated volume according to EN 12897:	800
Colour:	silver
Insulation according to DIN 4102-1 Fire Protection Class B2:	abnehmbare Segmentdämmung
Weight [kg]:	232
Total height including insulation [mm]:	1930
Diameter without insulation [mm]:	790
Diameter with insulation [mm]:	1015
Tilt height [mm]:	1900

Energy

Heat retaining loss according to EN 12897 [W]:	51
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	1,224
Output capacity (45°C) [l]:	457
Performance indicator NL following DIN 4708:	4,50

OEG Fresh-Water storage tank 800 l with 1 smooth-pipe heat exchanger



Tank

Real volume according to EN 12897 [l]:	796
p _{max} Tank [bar]:	3
t _{max} Tank [°C]:	95

DHW heat exchanger

DHW heat exchanger area [m ²]:	8
DHW heat exchanger volume [l]:	34,20
p _{max} DHW heat exchanger [bar]:	6
t _{max} DHW heat exchanger [°C]:	95

Smooth-pipe heat exchanger

Smooth-pipe heat exchanger [number]:	1
Smooth-pipe heat exchanger area bottom [m ²]:	2,60
Smooth-pipe heat exchanger volume bottom:	17
p _{max} Smooth-pipe heat exchanger [bar]:	10
t _{max} Smooth-pipe heat exchanger [°C]:	130

Connections

Connection layout:	90°
Connection sensor [Ø mm / terminal]:	6 mm
Connection cold / hot water:	Rp 1 1/4"
Connection heat generator [thread]:	Rp 1 1/2"
Connection heat exchanger [thread]:	Rp 1"
Connection heating element [thread]:	Rp 1 1/2"
Max. immersion depth of screw-in heater [mm]:	800